



- ◆ **THE WIDE DESIGN OF THESE BUCKETS MAKES THEM EXCELLENT FOR GRADING, DITCH CLEANING, DREDGING, TRENCHING, etc.**
- ◆ **HEAT TREATED 400BHN BASE EDGE IS DRILLED AND COUNTERBORED TO PROTECT NUTS FROM WEAR AND CREATE A SMOOTH INSIDE PROFILE. ONE PIECE OR THREE PIECE REVERSIBLE B/O EDGE INCLUDED.**
- ◆ **HEAT TREATED 400BHN SIDE LEADING EDGES AND OPTIONAL VERTICAL AND HORIZONTAL WEAR STRIPS**
- ◆ **WHILE OFTEN COPIED BUT NEVER DUPLICATED, THE LEMAC HEAVY TUBE SECTION DESIGN FORMS THE TOP BEAM OF THE BUCKET PROVIDING AN EXTREMELY SOLID BASE FOR THE MOUNTING EARS. CORNER GUSSETS INSURE RIGIDITY IS MAINTAINED FOR LONG BUCKET LIFE**
- ◆ **OPTIONAL DRAINAGE HOLES AVAILABLE**
- ◆ **SUITABLE FOR MINI'S TO HEAVY EXCAVATORS**
- ◆ **CUSTOM ORDER WITH A WIDE VARIETY OF TOOTH SYSTEMS INSTALLED INSTEAD OF STANDARD EDGES**
- ◆ **ONE YEAR OR 1,500 HOUR WARRANTY**
- ◆ **MANUFACTURED IN VIRGINIA, USA & SCOTLAND, UK**



MODEL	WIDTH		CAPACITY		MACHINE SIZE	
	INCH	MILLIMETER	YARD 3	METER 3	POUND	KILOGRAM
DC 12	46 = 84	1,168 = 2,134	0.635 = 1.200	0.581 = 1.097	24,500 = 30,500	11,113 = 13,835
DC 15	46 = 72	1,168 = 1,829	0.716 = 1.154	0.655 = 1.055	30,500 = 40,000	13,835 = 18,144
DC 18	48 = 72	1,219 = 1,829	0.837 = 1.292	0.765 = 1.181	??? = ???	??? = ???
DC 21	48 = 84	1,219 = 2,134	0.933 = 1.697	0.853 = 1.552	40,000 = 50,000	18,144 = 22,680
DC 25	48 = 84	1,219 = 2,134	1.099 = 2.002	1.005 = 1.831	50,000 = 58,000	22,680 = 26,308
DC 30	48 = 102	1,219 = 2,591	1.293 = 2.902	1.182 = 2.654	68,000 = 85,000	30,844 = 38,555
DC 40	48 = 96	1,219 = 2,438	1.699 = 3.609	1.554 = 3.300	85,000 = 104,000	38,555 = 47,174



LEMAC
ENGINEERING

UK / EUROPE

Email: uksales@lemaconline.com
Phone: +44 (0) 1259-751573

Website: www.Lemaconline.com

LEMAC
CORPORATION

US / CANADA

Email: sales@lemaconline.com
Phone: 1 (804) 862-8481

Distributed By:

(Attach Business Card Here)